


TORRE-TECH[®] 5.0

Specifications



Feedstock Input:

- Types
 - Wood Chips (<0.5 in/12 mm)
 - Bio-Crops (Switchgrass, Miscanthus, etc.)
 - Energy Bio-grasses
- Feed Rate of Wood Biomass (Moisture Content < 40%)
15,00 lbs/hr / 6,800 kg/hr (Dry Basis)

Electrical Consumption:

- 300 kW—Connected Requirement
- 225 kW—Estimated Operating Usage

System Dimensions: IP (FT) SI (M)

| | IP (FT) | SI (M) |
|------------|---------|--------|
| Length (L) | 80 | 24.0 |
| Width (W) | 32 | 9.8 |
| Height (H) | 30 | 9.0 |

Product Output:

- 5 Tons per Hour Torrefied Product
- Energy Content—10,000 BTU/lb / 5,500 kCal/kg (± 10%)
- Moisture Content < 10%
- Input to Output Ratio: Approx. 3 tons of “green” feedstock yields 1 ton of torrefied product. (Based on <40% moisture content of feedstock)
- Input to Output ratios may vary depending on type of feedstock and operating conditions.

Gas Consumption:

- Natural or Propane
- 11.0 million BTU/hr—Connected Requirement
- 200,000 BTU/hr—Estimated Operating Usage (fuel required for pilot as safety feature)

Water Usages:

- Cooling Process
- Fire Suppression Functions

**Agri-Tech
Producers, LLC**

116 Wildewood Club Court Columbia, SC 29223
Tel (803) 462-0153 Fax (803) 462-9676

www.agri-techproducers.com



KUSTERS-ZIMA

101 Zima Park Drive, Spartanburg SC 29301
Tel (864) 576-0660 Fax (864) 587-5761

KustersZima.com